

JUKI

ML-111U

Single-thread, Chainstitch Basting Machine



Basting machine
realizes high quality

ML-111U

Basting machine realizes high quality

- High efficient basting works at a sewing speed of 1,800sti/min.
- Chainstitch is continuously formed with a single thread and by a blind looper which eliminates the need for a bobbin thread refilling. In addition, the basted seam can be easily undone.
- Basting works are efficiently done with a maximum stitch length of 10mm which is easily set up by a control dial.

APPLICATIONS

- The basting of the front edges, edge and stand of collars, flaps of men's and ladies' suits and coats.
- The basting of the waist bands, the flies of trousers slacks, etc.

SPECIFICATIONS

Model name	ML-111U
Max. sewing speed	1,800sti/min*
Max. stitch length	10mm
Needle bar stroke	35mm
Lift of the presser foot	By hand : 5.5mm, By knee : 12mm
Needle (at the time of delivery)	TVx7 (#14) #11~#14
Thread take-up	Needle bar thread take up
Feed dog	3-row feed dog
Looper	Blind looper
Lubrication	By an oiler
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)
Weight of the machine	29kg

*"sti/min" stands for "Stiches per Minute"

WHEN YOU PLACE ORDERS

Machine head

ML111U

HOTLINE: 0982 085 899



Registered Organization : JUKI CORPORATION Head Office
The Scope of the Registration : The activities of research, development, design, sales, distribution, and maintenance services of industrial sewing machines, household sewing machines and industrial robots, etc., including sales and maintenance services of data entry systems.

JUKI
JUKI CORPORATION
SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI,
TOKYO 206-8551, JAPAN
PHONE : (81) 42-357-2370
FAX : (81) 42-357-2274
<http://www.juki.com>

- * Specifications and appearance are subject to change without prior notice for improvement.
- * Read the instruction manual before putting the machine into service to ensure safety.
- * This catalogue prints with environment-friendly soyink on recycle paper.